



HUBER+SUHNER®

DC-SET

FOR WIRELESS COMMUNICATION



DC-Set for Active Antenna

Technical Data

Power Supply

Input	AC 100 – 240 V 50/60 Hz, 350 mA
Output	12 V / 1300 mA
CE tested	

Including cable RG 174 (2.0 m) with SMA male.

Bias Tee

Frequency range	2400 - 2700 MHz
Impedance	50 Ω
VSWR	1.5
Isolation	25 dB
Insertion Loss	0.5 dB
Max. power	1 W (CW) at 25°C
RF input	SMA female
RF and DC output	SMA female
DC input	SMA female
Dimensions	101 x 95 x 32 mm (3.98" x 3.74" x 1.26")

Power Cord

T11 Euro (black)	
1-15P NEMA (black)	

Available Type

[9090.99.0020](#)

Article no.

23039383

Documents

[01.02.0777](#)

security instruction

[01.02.1507](#)

mounting instruction

HUBER+SUHNER group is certified according to ISO 9001 and ISO 14001.

WAIVER!

While the information contained has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG
Mobile Communications + Electronics Sector
Communication Equipment Components
CH-9100 Herisau, Switzerland
Tel.: +41 (0)71 353 41 11
Fax: +41 (0)71 353 47 51
www.hubersuhner.com

Document no.: 01.02.0907

Issue no.: 6

Supersedes: 10.2004

Uncontrolled Copy

Issued/Checked/Released: 4159/4417/10.2004

Last amended: 4159

